



## Starter Bars

Compliant with AS/NZS 4671: 2001 Steel Reinforcing Materials

TMR Registered Supplier



### Product Information

Starter bars are typically used to enable walls to be secured to footings or concrete slabs. They come in a variety of stock lengths, making it easy to connect wall sections and build a reinforced structure rapidly.

Stock length starter bars can be rapidly deployed in order to maintain structural strength while still allowing construction to proceed at a rapid rate. Hooked starter bars are available to remove the requirement to place bar guards or ReoSoks.

### Stock Starter Bars

Product Code	Diameter (mm)	Dimensions (mm)
SBR10102	R 10	1000 x 200
SBR10102H	R 10	1000 x 200 Hooked
SBR10122	R 10	1200 x 200
SBN12102	N 12	1000 x 200
SBN12102H	N 12	1000 x 200 Hooked

Product Code	Diameter (mm)	Dimensions (mm)
SBN12111	N 12	1100 x 100
SBN12122	N 12	1200 x 200
SBN12122H	N 12	1200 x 200 Hooked
SBN1282	N 12	800 x 200
SBN1296	N 12	900 x 600

Product Code	Diameter (mm)	Dimensions (mm)
SBN16102	N 16	1000 x 200
SBN16102H	N 16	1000 x 200 Hooked
SBN16103	N 16	1000 x 300
SBN16122	N 16	1200 x 200
-	-	-