



NEUMANN STEEL
REINFORCING

NuRail® 40-55

Made in Australia

Compliant with AS/NZS 2425:2015

Made from recycled plastic

Flat top ensures swift mesh placement

Strong anchoring spikes ensure a secure hold

Enhances concrete flow

Large apertures help eliminate air pockets in the concrete to facilitate consistent concrete flow

Easy and fast positioning



NuRail®40-55 is a reinforcing mesh spacer used in the residential building industry. It offers consistent and stable support for reinforcing mesh when using NuPod and a polystyrene waffle pod system. Its unique design allows the positioning of the mesh with appropriate spacing and helps maintain the correct concrete cover for the pour. It enables builders to achieve the correct concrete cover without causing any damage to the polystyrene pods.



Spacer heights: 40mm and 55mm

Load Rated: 120kg

Placement: 2 per pod



Mesh sizes up to NF92

Suitable for 85mm and 100mm slab thickness

Concrete Cover Table

Mesh	A	B	C	D
NF72	26	19	40	85
NF72	26	19	55	100
NF82	23	22	40	85
NF82	23	22	55	100
NF92	20	25	40	85
NF92	20	25	55	100

All dimensions are nominal



neumannsteel.com.au



07 5589 9280

info@neumann.com.au

